

# Jersey + Swagger

RESTful API in AEM



# Goals and References

JAX-RS Server <https://jax-rs-spec.java.net/>

Jackson JSON-POJO mapper: <https://github.com/FasterXML/jackson>

Swagger yaml/json definition <http://petstore.swagger.io/v2/swagger.json>

Swagger UI visual forms <http://petstore.swagger.io/>

```
@POST
@Path("/withdrawal")
@Consumes("text/plain")
@Produces("application/json")
public Money withdraw(
    @PathParam("card") String card,
    @QueryParam("pin") String pin,
    String amount) {
    return getMoney(card, pin, amount);
}
}
```

## Dependencies

```
<dependency>  
  <groupId>com.eclipsesource.jaxrs</groupId>  
  <artifactId>jersey-all</artifactId>  
</dependency>
```

```
<dependency>  
  <groupId>com.eclipsesource.jaxrs</groupId>  
  <artifactId>publisher</artifactId>  
</dependency>
```

```
<dependency>  
  <groupId>com.fasterxml.jackson.jaxrs</groupId>  
  <artifactId>jackson-jaxrs-json-provider</artifactId>  
</dependency>
```

```
<dependency>  
  <groupId>com.eclipsesource.jaxrs</groupId>  
  <artifactId>swagger-all</artifactId>  
</dependency>
```

## Bundles

```
<embedded>
  <groupId>com.eclipsesource.jaxrs</groupId>
  <artifactId>jersey-all</artifactId>
  <target>${install.path}</target>
</embedded>
<embedded>
  <groupId>com.eclipsesource.jaxrs</groupId>
  <artifactId>swagger-all</artifactId>
  <target>${install.path}</target>
</embedded>
<embedded>
  <groupId>com.eclipsesource.jaxrs</groupId>
  <artifactId>publisher</artifactId>
  <target>${install.path}</target>
</embedded>
```

# Configuration

localhost:4503/system/console/configMgr

Mobile Canvas Bundle

NonScriptTagHandler Factory

notificationsrouter.name

✓ org.apache.aries.jmx.framework.StateConfig

---

**OSGi REST Publisher**

OSGi REST Publisher Configuration

Root   
The root URI for publishing web services. Defaults to /services (root)

Disable jersey wadl   
⚠ WADL generation through 'application.wadl' is enabled in Jersey by default. To disable this set this property to true (disableWadl)

Publish Delay   
⚠ The delay in milliseconds to wait before reloading the servlet container after a new resource was registered (publishDelay)

---

**Configuration Information**

Persistent Identity (PID)	com.eclipsesource.jaxrs.connector
Configuration Binding	ijcrinstall:/apps/elbrus/install/publisher-5.3.1.jar
	OSGi JAX-RS Connector (com.eclipsesource.jaxrs.publisher), Version 5.3.1.201602281253



# Jersey via Jackson

- Jackson JSON marshaller/parser.
- POJOs with optional annotations.
- Resource classes.

## JSON Provider

@Component

**@Service(Object.class)**

**@Property(name = "javax.ws.rs", boolValue = true)**

@Consumes(MediaType.WILDCARD)

@Produces(MediaType.WILDCARD)

**@Provider**

public class JsonProvider extends **JacksonJaxbJsonProvider** {}

## Data model

```
public class Company {  
    private final int id;  
    @JsonProperty("company name")  
    private final String name;  
  
    public Company(int id, String name) {  
        this.id = id;  
        this.name = name;  
    }  
    public int getId() {    return id;  }  
    public String getName() {    return name;  }  
}
```



Resource class

```
@Path("/company")  
@Consumes(MediaType.APPLICATION_JSON)  
@Produces(MediaType.APPLICATION_JSON)  
public class CompanyResource {  
  
    @GET  
    public List<Company> list() {  
        return service.selectNewCompanies();  
    }  
  
    @POST  
    public int create(Company company) throws NotAuthorizedException {  
        return service.createNewCompany(company);  
    }  
}
```

# Swagger

- Resource and operations annotations.
- Model and properties annotations.
- JSON/YAML definition lister.
- Swagger UI.

## Resource and operation annotations

```
@Api("Company resource")  
public class CompanyResource {  
  
    @GET  
    @ApiOperation("Returns all companies")  
    public List<Company> all() {  
        return ImmutableList.of(new Company(1, "Axamit"),  
                                new Company(2, "Adobe"),  
                                new Company(3, "Oracle"));  
    }  
}
```

Model and properties annotations

**@ApiModel("Company model")**

```
public class Company {  
    @ApiModelProperty("Company ID")  
    private final int id;  
    @ApiModelProperty("Company Name")  
    private final String name;  
  
    public Company(int id, String name) {  
        this.id = id;  
        this.name = name;  
    }  
  
    public int getId() {    return id;    }  
    public String getName() {    return name;    }  
}
```

Definition lister

```
@Api("Swagger lister")
```

```
@SwaggerDefinition(basePath = "/api/v1")
```

```
@Component
```

```
@Service(Object.class)
```

```
@Path("/")
```

```
public class SwaggerResource extends ApiListingResource {}
```

# Swagger UI

<https://github.com/swagger-api/swagger-ui/tree/master/dist> -> /etc/designs/elbrus/swagger/

### Apache Sling Content Disposition Filter

Request filter adding Content Disposition attachment for certain paths/content types

Content Disposition Paths  **⚠** These paths are checked by the filter. Each entry is of the form 'path [ ":" CSV of excluded content types ]'. Invalid entries are logged and ignored. (sling.content.disposition.paths)

Content Disposition Excluded Paths  **⚠** These paths are excluded by the filter. Each entry is of the form 'path'. (sling.content.disposition.excluded.paths)

Enable Content Disposition for all paths  This flag controls whether to enable Content Disposition for all paths, except for the excluded paths defined by sling.content.disposition.excluded.paths (sling.content.disposition.all.paths)

### Configuration Information

Persistent Identity (PID)	org.apache.sling.security.impl.ContentDispositionFilter
Configuration Binding	launchpad:resources/install/5/org.apache.sling.security-1.0.18.jar
	Apache Sling Security (org.apache.sling.security), Version 1.0.18

# Questions?

Author: Vasily Lazerko  
Company: Axamit

